

TOWER LIGHTS

IP 56



PAE Series

Ø25mm

LED Steady and Flashing

- LED light provides long life and reliability
- Prism-cut lenses for even light distribution
- Mounting: straight pole or 90° wall mount
- One to five light stacks
- Colors available: blue, clear, green, red & yellow
- Wire leads



Stack	Mounting	Steady	Flashing	Voltage	Current Draw
1 Stack	Pole	PAEM(Δ)-101-R	PAEFM(Δ)-101-R	12 VDC/AC	30mA
	90° Bracket	PAER(Δ)-101-R	PAEFR(Δ)-101-R		
	Pole	PAEM(Δ)-102-R	PAEFM(Δ)-102-R	24 VDC/AC	25mA
	90° Bracket	PAER(Δ)-102-R	PAEFR(Δ)-102-R		
2 Stack	Pole	PAEM(Δ)-201-RG	PAEFM(Δ)-201-RG	12 VDC/AC	65mA
	90° Bracket	PAER(Δ)-201-RG	PAEFR(Δ)-201-RG		
	Pole	PAEM(Δ)-202-RG	PAEFM(Δ)-202-RG	24 VDC/AC	60mA
	90° Bracket	PAER(Δ)-202-RG	PAEFR(Δ)-202-RG		
3 Stack	Pole	PAEM(Δ)-301-RYG	PAEFM(Δ)-301-RYG	12 VDC/AC	100mA
	90° Bracket	PAER(Δ)-301-RYG	PAEFR(Δ)-301-RYG		
	Pole	PAEM(Δ)-302-RYG	PAEFM(Δ)-302-RYG	24 VDC/AC	90mA
	90° Bracket	PAER(Δ)-302-RYG	PAEFR(Δ)-302-RYG		
4 Stack	Pole	PAEM(Δ)-401-RYGB	PAEFM(Δ)-401-RYGB	12 VDC/AC	135mA
	90° Bracket	PAER(Δ)-401-RYGB	PAEFR(Δ)-401-RYGB		
	Pole	PAEM(Δ)-402-RYGB	PAEFM(Δ)-402-RYGB	24 VDC/AC	120mA
	90° Bracket	PAER(Δ)-402-RYGB	PAEFR(Δ)-402-RYGB		
5 Stack	Pole	PAEM(Δ)-501-RYGBC	PAEFM(Δ)-501-RYGBC	12 VDC/AC	170mA
	90° Bracket	PAER(Δ)-501-RYGBC	PAEFR(Δ)-501-RYGBC		
	Pole	PAEM(Δ)-502-RYGBC	PAEFM(Δ)-502-RYGBC	24 VDC/AC	150mA
	90° Bracket	PAER(Δ)-502-RYGBC	PAEFR(Δ)-502-RYGBC		

(Δ) Indicate G - 51mm pole or P - 150mm pole

DIMENSIONS Unit: mm



Mounting Options (see page 11)

Straight Mount		90° Mount	
MAP-0051	25 x 51mm pole	MAP-0051	25 x 51mm pole
MAP-0150	25 x 150mm pole	MAP-0150	25 x 150mm pole
MAM-B025	Threaded adapter with nut	MAM-DS40	90° plastic wall bracket



• 10100 Royalton Road • Cleveland OH 44133 • (440) 237-3200 • Fax (440) 237-1744
 • 417 Tomahawk Drive • Maumee OH 43537 • (419) 893-3330 • Fax (419) 893-2151
 • Web site: www.iseinc.com • E-mail: isetoledo@iseinc.com • Toll Free: (877) 893-3330